



Hydrogen Peroxide 27-28% (All Grades)

1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier used on the label

:Hydrogen Peroxide 27-28%

Product Code(s) Not available.

Recommended use of the chemical and restrictions on use :

Reagent: Chemical intermediate.

Chemical family Inorganic peroxide solution.

Name, address, and telephone number of Name, address, and telephone number the manufacturer: of the supplier:

Borden & Remington Corp.

PO Box 2573

Refer to supplier 63 Water St

Fall River, MA, USA 02722

Supplier's Telephone #:508-675-0096

24 Hr. Emergency Tel #:Chemtrec 1-800-424-9300 (Within Continental U.S.);

Chemtrec 703-527-3887

(Outside U.S.).

2. HAZARDS IDENTIFICATIONEmergency Overview

Color: colorless

Physical state: liquid

Odor: pungent

Classification of the substance or mixture:

Oxidizing liquids, Category 2, H272

Oral: Acute toxicity, Category 4, H302

Serious eye damage, Category 1, H318

Specific target organ toxicity - single exposure, Category 3, Respiratory system, H335

Chronic aquatic toxicity, Category 3, H412

*For the full text of the H-Statements mentioned in this Section, see Section 16.

GHS-Labeling

Borden & Remington

Page 1 of 13

27 – 28% Hydrogen Peroxide



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)



Hazard pictograms:

Signal word:

Danger

Corrosive

Hazard statements:

H272 : May intensify fire; oxidizer.

H302 : Harmful if swallowed.

H318 : Causes serious eye damage.

H335 : May cause respiratory irritation.

H412 : Harmful to aquatic life with long lasting effects.

Precautionary statements:

Prevention:

P210 .• Keep away from heat.

P220 .• Keep/Store away from clothing/ combustible materials.

P221 .• Take any precaution to avoid mixing with combustibles.

P261 .• Avoid breathing gas/misvapors/spray.

P264 • Wash skin thoroughly after handling.

P270 .• Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 • Avoid release to the environment.

P280 • Wear protective gloves/ eye protection/ face protection.

Response:

P301 + P312 : IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

P304 + P340 : IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305 + P351 + P338 : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 : Immediately call a POISON CENTER or doctor/ physician.

P330 : Rinse mouth.

P370 + P378 : In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 : Store in a well-ventilated place. Keep container tightly closed.

P405 : Store locked up.

Disposal:

P501 : Dispose of contents/ container to an approved waste disposal plant.

Supplemental information:

Potential Health Effects:

If swallowed:



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

May cause: gastrointestinal symptoms, ulceration, burns, accumulation of fluid in the lungs which may be delayed for several hours.(severity of effects depends on extent of exposure) .

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-NO.	WtJWt	GHS Classification**
Hydrogen peroxide (H2O2)	7722-84-1	> 27 - < 28 %	H272, H302, H318, H335, H412
Water	7732-18-5	72 - 73 %/0	Not classified

**For the full text of the H-Statements mentioned in this Section, see Section 16.

4. FIRST AID MEASURES

Inhalation:

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Skin:

In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse.

Eyes:

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.

Ingestion:

If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Get medical attention immediately. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. Rinse mouth.

Notes to physician:

Exposure to material may cause delayed lung injury resulting in pulmonary edema and pneumonitis. Exposed individuals should be monitored for 72 hours after exposure for the onset of delayed respiratory symptoms.

5. FIREFIGHTING MEASURES

Extinguishing media (suitable):

water spray, water fog

Protective equipment:

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent).

Further firefighting advice:

Oxidizing material

In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

Decomposition will release oxygen, which will intensify a fire.
Cool closed containers exposed to fire with water spray.
Closed containers of this material may explode when subjected to heat from surrounding fire.
Do not allow run-off from fire fighting to enter drains or water courses.
Fire fighting equipment should be thoroughly decontaminated after use.

Fire and explosion hazards:

Explosive when mixed with combustible material. Avoid breathing fumes from fire exposed material.

6. ACCIDENTAL RELEASE MEASURES

In case of spill or leak:

Prevent further leakage or spillage if you can do so without risk. Evacuate area of all unnecessary personnel. Ventilate the area. Eliminate all ignition sources. Avoid generation of vapors. Avoid contact with cellulose, paper, sawdust or similar substances. Risk of self-ignition or promotion of fires. Combustible materials exposed to hydrogen peroxide should be rinsed immediately with large amounts of water to ensure that all the hydrogen peroxide is removed. Contain and collect spillage with non-combustible absorbent material such as clean sand, earth, diatomaceous earth or non-acidic clay and place into suitable properly labeled containers for prompt disposal. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

7. HANDLING AND STORAGE

Handling

General information on handling:

Do not taste or swallow.
Do not get in eyes, on skin, or on clothing.
Avoid breathing vapor or mist.
Keep from contact with clothing and other combustible materials.
Keep away from heat, sparks and flames.
Use only with adequate ventilation.
Wash thoroughly after handling.
Wear fire/ flame resistant/ retardant clothing.
Prevent product contamination.
Keep only in the original container.
Store in tightly closed container.
DO NOT CUT, DRILL, GRIND, OR WELD ON OR NEAR THIS CONTAINER.
Emptied container retains vapor and product residue.
Observe all labeled safeguards until container is cleaned, reconditioned or destroyed. Avoid contamination.

General information on storage conditions:

Store in tightly closed container. Store in cool, dry, well ventilated area away from sources of ignition such as flame, sparks and static electricity. Store out of direct sunlight in a cool well-ventilated place. Store in original container. Store away



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

from combustibles and incompatible materials. Refer to National Fire Protection Association (NFPA) 430, Code for the Storage of Solid and Liquid Oxidizers.

Storage incompatibility — General:

Store separate from acids, alkalis, reducing agents, and combustibles. Store separate from:

Organic materials

Metallic oxides

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Airborne Exposure Guidelines:

HYDROGEN PEROXIDE (7722-84-1)

US. ACGIH Threshold Limit Values

time weighted average	1 ppm
-----------------------	-------

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

PEL:	1 ppm (1.4 mg/m ³)
------	--------------------------------

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

Engineering controls:

Investigate engineering techniques to reduce exposures below airborne exposure limits or to otherwise reduce exposures. Provide ventilation if necessary to minimize exposures or to control exposure levels to below airborne exposure limits (if applicable see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

Consult ACGIH ventilation manual or NFPA Standard 91 for design of exhaust systems.

Respiratory protection:

Avoid breathing vapor or mist. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components. Full facepiece equipment is recommended and, if used, replaces need for face shield and/or chemical goggles. Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact.

When handling this material, gloves of the following type(s) should be worn:

Neoprene

Borden & Remington

Page 5 of 13

27 – 28% Hydrogen Peroxide



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

Polyvinylchloride

Impervious butyl rubber gloves

Wear a face shield, chemical goggles and chemical resistant clothing such as an approved splash protective suit made of SBR Rubber, PVC, Gore-Tex or a HAZMAT Splash Protective Suit (Level A, B, or C) when splashing may occur (such as connecting/disconnecting, mechanical first break). For foot protection, wear boots made of NBR, PVC, polyurethane, or neoprene. Overboots made of Latex or PVC, as well as firefighter boots or specialized HAZMAT boots are also permitted. DO NOT wear any form of boot or overboots made of nylon or nylon blends. DO NOT use cotton, wool or leather, as these materials react RAPIDLY with higher concentrations of hydrogen peroxide. Rinse immediately if skin is contaminated. Remove contaminated clothing and shoes immediately. Thoroughly rinse the outside of gloves and protective clothing with water prior to removal. Completely submerge hydrogen peroxide contaminated clothing or other materials in water prior to drying. Residual hydrogen peroxide, if allowed to dry on materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in a fire. Clean protective equipment before reuse. Provide a safety shower at any location where skin contact can occur. Wash thoroughly after handling.

Eye protection:

Where there is potential for eye contact, wear a face shield, chemical goggles, and have eye flushing equipment immediately available.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	colorless
Physical state:	liquid
Odor:	pungent
Odor threshold:	No data available
Flash point	None.
Auto-ignition temperature:	Not applicable
Lower flammable limit (LFL):	Not applicable
Upper flammable limit (UFL):	Not applicable
pH:	No data available
Density:	1.105 g/cm ³ (68 °F (20 °C))
Vapor pressure:	13.5 mmHg (68 °F (20 °C))
Relative vapor density:	1.0
Vapor density:	not determined
Boiling point/boiling range:	219 °F (104 °C)



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

Freezing point:	-9 °F (-23 °C)
Evaporation rate:	No data available
Solubility in water:	completely soluble
% Volatiles:	100%
Molecular weight:	34.01 g/mol
Oil/water partition coefficient:	No data available
Thermal decomposition	No data available
Flammability (solid, gas):	Not applicable

10. STABILITY AND REACTIVITY

Stability:

This material is chemically stable under normal and anticipated storage, handling and processing conditions.

Materials to avoid:

Metals

Organic materials

Reducing agents

Metallic oxides

Dusts

Combustible materials (e.g., wood, sawdust)

Alkaline materials

Conditions | hazards to avoid:

Material decomposes with the potential to produce a rupture of unvented closed containers.

Hazardous decomposition products:

This material decomposes if contaminated, causing fire and possible explosions. Oxygen can be liberated at temperatures above ambient.

11. TOXICOLOGICAL INFORMATION

Data on this material and/or a similar material are summarized below.

Data for Hydrogen Peroxide 27-28% (All Grades)

Acute toxicity

Oral:

Harmful if swallowed. (Rat) LD50 = 1,200 mg/kg. (35 %/0) (as aqueous solution)

Dermal:



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

May be harmful in contact with skin. (Rabbit) LD50 > 2,000 mg/kg. (35 %/0) (as aqueous solution)

May be harmful in contact with skin. (Rat) LD50 > 2,000 mg/kg. (35 %/0) as aqueous solution

Inhalation:

No deaths occurred. (Rat) 4 h I-CO > 0.17 mg/l. (50 %/0) (saturated vapor)

Skin Irritation:

Causes mild skin irritation. (Rabbit) Irritation Index: 1.6 / 8. (35 %/0) (aqueous solution)

Eye Irritation:

Causes serious eye damage. (Rabbit) (35 %/0) (aqueous solution)

Data for HYDROGEN PEROXIDE (7722-84-1)

Acute toxicity

Specific target organ toxicity - single exposure: May cause respiratory irritation.

Repeated dose toxicity

Repeated drinking water administration to rat and mouse / affected organ(s): Gastro-intestinal tract / signs: irritation

Repeated inhalation administration to Rat I affected organ(s): nose / signs: irritation

Carcinogenicity

Chronic drinking water administration to rat and mouse / affected organ(s): Gastro-intestinal tract / signs: Increased incidence of tumors was reported.

Classified by the International Agency for Research on Cancer as: Group 3: Unclassifiable as to carcinogenicity in humans.

Genotoxicity

Assessment in Vitro:

Genetic changes were observed in laboratory tests using: bacteria, animal cells

Genotoxicity

Assessment in Vivo:

Genetic changes were observed in a laboratory test using: mice, rats

Human experience

Inhalation:

Throat: irritation. (based on reports of occupational exposure to workers)

Human experience

Skin contact:

Skin: bleaching of hair. (based on reports of occupational exposure to workers)



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

Human experience

Eye contact:

Eye: irritating. (based on reports of occupational exposure to workers)

Human experience

Ingestion:

Gastrointestinal tract: bloating, ulceration, burns. (accidental exposure to concentrated solutions)

Lung: accumulation of fluid in the lungs, death. (severity of effects depends on extent of exposure)

12. ECOLOGICAL INFORMATION

Chemical Fate and Pathway

Data on this material and/or a similar material are summarized below.

Data for HYDROGEN PEROXIDE (7722-84-1)

Biodegradation:

Readily biodegradable. (0.02 d) biodegradation 99 %

Octanol Water Partition Coefficient:

log Pow = -1.57 (calculated)

Ecotoxicology

Data on this material and/or a similar material are summarized below.

Data for HYDROGEN PEROXIDE (7722-84-1)

Aquatic toxicity data:

Harmful. Pimephales promelas (fathead minnow) 96 h LC50 = 16.4 mg/l

Aquatic invertebrates:

Toxic. Daphnia pulex (Water flea) 48 h EC50 = 2.4 mg/l

Algae:

Toxic. Skeletonema costatum 72 h ErC50 = 1.38 mg/l

Microorganisms:

Activated sludge 0.5 h EC50 = 466 mg/l Activated

sludge 3 h EC50 > 1,000 mg/l

Chronic toxicity to aquatic invertebrates:

Harmful. Daphnia magna (Water flea) 21 d NOEC (reproduction) - — 0.63 mg/l

13. DISPOSAL CONSIDERATIONS

Waste disposal:

Dilution with water is the preferred method of disposal. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

Take appropriate measures to prevent release to the environment.

14. TRANSPORT INFORMATION

US Department of Transportation (DOT)

UN Number	..	2014
Proper shipping name	..	Hydrogen peroxide, aqueous solutions
Class	..	5.1
Subsidiary hazard class	..	(8)
Packaging group	..	II
Marine pollutant	..	no

International Maritime Dangerous Goods Code (IMDG)

UN Number	2014	:
Proper shipping name	HYDROGEN	:
	PEROXIDE, AQUEOUS SOLUTION	:
Class	5.1	:
Subsidiary hazard class	(8)	:
Packaging group		:
Marine pollutant		:

15. REGULATORY INFORMATION

Chemical Inventory Status

EI-J. EINECS	EINECS	Conforms to
United States TSCA Inventory	TSCA	The components of this product are all on the TSCA Inventory.
Canadian Domestic Substances List (DSL)	DSL	All components of this product are on the Canadian DSL.
China. Inventory of Existing Chemical Substances in China (IECSC)	IECSC (CN)	Conforms to
Japan. ENCS - Existing and New Chemical Substances Inventory	ENCS (JP)	Does not conform

Japan. ISHL - Inventory of Chemical Substances	ISHL (JP)	Does not conform
Korea. Korean Existing Chemicals Inventory (KECI)	KECI (KR)	Conforms to



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

Philippines Inventory of Chemicals and Chemical PICCS (PH) Substances (PICCS) Does not conform

Australia Inventory of Chemical Substances (AICS) ACS Conforms to

United States — Federal Regulations

SARA Title III — Section 302 Extremely Hazardous Chemicals:

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>SARA</u> <u>Reportable</u> <u>Quantities</u>	<u>SARA</u> <u>Threshold</u> <u>Planning</u> <u>Quantity</u>
----------------------	----------------	---	---



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

HYDROGEN PEROXIDE

7722-84-1

1000 lbs

1000 lbs

SARA Title III - Section 311/312 Hazard Categories: Acute Health Hazard, Fire Hazard, Reactivity Hazard

SARA Title III - Section 313 Toxic Chemicals:

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act (CERCI-A) - Reportable Quantity (RQ):

The components in this product are either not CERCI-A regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

United States – State Regulations

New Jersey Right to Know

<u>Chemical Name</u>	<u>CAS-No.</u>
HYDROGEN PEROXIDE	7722-84-1
New Jersey Right to Know — Special Health Hazard Substance(s)	
<u>Chemical Name</u>	<u>CAS-No.</u>
HYDROGEN PEROXIDE	7722-84-1

Pennsylvania Right to Know

<u>Chemical Name</u>	<u>CAS-No.</u>
HYDROGEN PEROXIDE	7722-84-1

Pennsylvania Right to Know — Environmentally Hazardous Substance(s)

<u>Chemical Name</u>	<u>CAS-No.</u>
HYDROGEN PEROXIDE	7722-84-1

California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.



SAFETY DATA SHEET

Hydrogen Peroxide 27-28% (All Grades)

16. OTHER INFORMATION

Full text of H-Statements referred to under sections 2 and 3.

H272 May intensify fire; oxidizer.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

Miscellaneous:

Other information: This MSDS covers the following grades of 27% - 28%
H202:

Latest Revision(s):

Revised Section(s): Initial entry

Date of Review: 11/16/2022

Borden & Remington believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Borden & Remington., Borden & Remington expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.